

EASYSHARE C330 Zoom Digital Camera Specifications



Specifications

Standard features

CCD resolution	4.0 megapixels (2336 × 1744 pixels)
Image resolution	4.0 megapixels (2304 × 1728 pixels)
Picture quality	4.0 MP—best (prints up to 20 × 30 in. (50 × 75 cm)) 3.5 MP—best 3:2 (optimized ratio for 4 × 6 in. (10 × 15 cm) prints) 3.1 MP—better (prints up to 11 × 14 in. (28 × 36 cm)) 2.1 MP—good (small prints) 1.1 MP—e-mail
Still format	JPEG/EXIF v 2.21
Lens	f/2.7–4.6 (34–102 mm, 35 mm equivalent)
Preview	0.2X increments starting at 3X optical zoom
Zoom	3X optical zoom advanced digital zoom—5X continuous
Aperture	f/2.7–5.2 (wide), f/4.6–8.8 (tele)
Shutter speed	4–1/1400 seconds, long exposure max 4 seconds
Viewfinder	Optical
LCD	1.5 in. (3.8 cm) indoor/outdoor color display

Performance features

Still capture modes	auto, SCN, sport, landscape, close-up
Scene modes	auto, portrait, sport, landscape, close-up, night portrait, snow, beach, self-portrait, party, fireworks, backlight, children
Color modes	color, sepia, black and white
Burst mode	1.8 fps, maximum 3 images
Click to capture	0.68 seconds (preview on), 0.75 seconds (preview off)
Shot to shot	1.5 seconds (wide preview ON, buffer not full), 7.7 seconds (wide preview ON, buffer full)
Video mode	continuous MPEG-4 compressed video with audio recording during video capture
Video resolution	QVGA (320 × 240 pixels) at 20 fps
Video length	continuous based on memory capacity
Video format	QUICKTIME MOV (MPEG-4 compression)
Auto focus	TTL-AF, continuous AF, single AF

Auto focus selection	multi-zone, (3 zones) center zone
Focus range	Standard—2 ft (0.6 m)–infinity Close-up, wide—5–28 in. (0.13 m–0.7 m) Close-up, tele—9–28 in. (0.22 m–0.7 m) Landscape—33 ft (10 m)–infinity
Sensitivity	ISO equivalent 80–200 (automatic) and 80,100, 200, 400 (manual)
White balance	auto, daylight, tungsten, fluorescent
Exposure metering	center-weighted AE
Exposure compensation	+/-2.0 EV in 0.5 EV step increments
Long time exposure	0.7–4 seconds (with 0.5 EV step)
Ease of use features	
On-camera cropping	8-level zoom and moveable crop window
Built-in flash	auto, red-eye reduction, fill, off
Flash range	ISO 140, wide—2–11.8 ft (0.6–3.6 m) ISO 140, tele—2–6.9 ft (0.6–2.1 m)
Review options	1X–8X magnify with pan, fast scroll, slide show, multi-up, protect, album, share/print, label, image storage, copy, crop
Favorites	slide show, multi-up, remove favorites, setup menu
Dedicated buttons	back: menu, review, Share, dedicated delete, zoom, 5-way controller, LCD on and off/info top: self-timer/burst, flash, shutter, mode dial
Auto picture rotation	yes
Software	works with KODAK EASYSHARE Software
Self-timer	10 seconds, 2 seconds
Additional features	
Dock compatibility	works with optional KODAK EASYSHARE Printer Dock Series 3 and KODAK EASYSHARE Camera Dock Series 3*
IMAGELINK Print System compatible	yes
PICTBRIDGE enabled	yes
Storage	16 MB internal memory**, SD/MMC card expansion slot
Power options	optional KODAK EASYSHARE Docks with 1 KODAK Ni-MH Rechargeable Digital Camera Battery KAA2HR; 2 KODAK Oxy-Alkaline Digital Camera Batteries AA; 2 KODAK Ni-MH Rechargeable Digital Camera Batteries AA; 1 KODAK Lithium Digital Camera Battery CRV3; 2 lithium batteries AA; 3 volt DC input
Lens protection	built-in lens barrier
Tripod mount	1/4 in. (6.4 mm) standard
I/O interface	A/V output (NTSC or PAL, user selectable), exclusive KODAK Camera Dock/Printer Dock interface, digital (USB 2.0) connector

Weight without batteries: 5.6 oz (160 g)
Dimensions W × H × D: 3.6 × 2.6 × 1.4 in. (91.5 × 65 × 35 mm)

Warranty

Warranty one year

Package Contents

KODAK EASYSHARE C330 Zoom Digital Camera

KODAK Non-Rechargeable Digital Camera Battery

USB cable

Wrist strap

KODAK EASYSHARE Software

Getting Started Kit

Custom camera insert for optional KODAK EASYSHARE Camera and Printer Docks

System Requirements

Windows

- WINDOWS 98, 98SE, ME, 2000 SP1, or XP OS
- 233 MHz processor or greater (300 MHz recommended for XP)
- 64 MB RAM (128 MB for XP)
- INTERNET EXPLORER 5.01 or higher
- 200 MB hard drive disk space available
- CD-ROM drive
- Available USB port
- Color monitor, 800 × 600 display resolution, 16-bit minimum

Macintosh

- POWERMAC or POWERBOOK G3, G4, G5; iMac; eMac; or iBook computer
- MACINTOSH OS X 10.2.3-10.2.8, 10.3 or greater
- 128 MB RAM for OS X
- SAFARI 1.0 or higher
- 200 MB hard drive disk space available
- CD-ROM drive
- Available USB port
- Color monitor, 800 × 600 display resolution, 16-bit minimum

* KODAK Dock Adapter Kit D-22 required to enable compatibility with KODAK EASYSHARE Printer Dock, Printer Dock Plus, Printer Dock 6000, and Camera Dock 6000.

** 16 MB internal memory/13 MB available memory for image storage (1 MB equals one million bytes)