

EASYSHARE CX7525 Camera Specifications



Making digital even simpler.

Introducing the KODAK EASYSHARE CX7525 Zoom Digital Camera. When advanced picture-taking features combined with point-and-shoot simplicity, you get the best of both worlds.

Detailed specifications



Specifications

Standard Features

CCD resolution	1/2.5 inch type (5.36 M total pixels)
Image resolution	5.0 MP (2560x1920 pixels)
Picture quality	5.0 MP - best (prints up to 20"x30") 4.4 MP - best 3:2 (optimized ratio for 4"x6" prints) 3.1 MP - better (prints up to 11"x14") 1.7 MP - good (small prints)
Zoom	15X total zoom 3X optical zoom -- 5.6-16.8 mm (35 mm equivalent: 34-102 mm) 5X advanced digital zoom
Aperture	f/2.7-5.2 (wide); f/4.6-8.7 (tele)
Shutter speed	1/2 - 1/1400 seconds
Viewfinder	real image optical viewfinder
Display	1.6" (4 cm) indoor/outdoor color display

Performance Features

Scene modes	auto, portrait, landscape, night, close-up, sport, movie
Color modes	color, black-and-white, sepia
Burst mode	2.4 fps, up to 5 pictures
Click to capture	0.6 seconds
Shot to shot	1.3 seconds
Movie mode	continuous MPEG-4 video with audio capture/playback
Movie image	VGA (640x480 pixels) at 13 fps

resolution	QVGA (320x240 pixels) at 20 fps
Movie length	Memory is dependant upon size of external memory card or 5-, 15-, 30-second clips
Movie file format	Still: JPEG/EXIF v2.21; Movie: QuickTime MOV (MPEG-4 compression)
Auto focus	TTL-AF, multi-zone, center-zone
Focus distance	Standard - 60 cm (23.6 in.) to infinity Landscape - 10 m (32.8 ft.) to infinity Close-up wide - 13-70 cm (5-28 in.) Close-up tele - 22-70 cm (9-28 in.)
ISO equivalent	80-160 (automatic) and 80, 100, 200, 400 (manual)
White balance	auto, daylight, tungsten, fluorescent
Light metering method	TTL-AE, selectable: multi-pattern, center-weighted, center spot
Exposure control	programmed AE
Long time exposure	0.7-4 seconds
Exposure compensation	+/- 2.0 EV in 0.5 EV step increments

Ease of Use Features

Flash mode	auto, red-eye, fill, off
Flash range	wide - 0.6-3.6 m (2-11.8 ft.); tele - 0.6-2.1 m (2-6.9 ft.)
Review mode	1X-8X magnify with pan, slide show, multi-up, fast scroll, protect, album
Favorites mode	on-camera picture storage
Auto-orientation	auto picture-rotation
Software	KODAK EASYSHARE Software
Compatibility	Dock compatibility - KODAK EASYSHARE Camera Docks, KODAK EASYSHARE Printer Docks*
PICTBRIDGE compatible	print directly from camera
Storage	16 MB internal memorySD/MMC card expansion slot
Self-timer	10 seconds

Additional Features

Power options	optional KODAK EASYSHARE Docks with Ni-MH rechargeable battery pack; 2 AA KODAK MAX Digital Camera Batteries; 2 AA lithium or Ni-MH batteries or 1 CRV3 lithium battery; 3 volt DC
Lens protection	built-in lens barrier
Tripod mount	1/4 in. standard
Interface	power input (3V DC), A/V output (NTSC or PAL, user selectable), KODAK Camera Dock/Printer Dock interface, USB compliant connector
Weight	without batteries - 178 g (6.3 oz.)
Dimensions	WxHxD: 102.5x65x38 mm (4.0x2.6x1.5 in.)

Warranty

Warranty	1 year
----------	--------

Package Contents

KODAK EASYSHARE CX7525 Zoom Digital Camera

KODAK MAX Digital Camera Batteries (AA or equivalent)

Video out cable

USB cable

Wrist strap

KODAK EASYSHARE Software

Getting Started Kit

Custom camera insert for optional KODAK EASYSHARE Camera and Printer Docks

System Requirements

Windows

- WINDOWS 98, 98SE, ME, 2000 SP1, or XP OS
- Internet Explorer 5.0 or higher
- 233 MHz processor or greater
- 64 MB RAM (128 MB RAM for WINDOWS XP OS)
- 200 MB hard drive disk space available
- CD-ROM drive
- Available USB port
- Color monitor, 800x600 pixels (16-bit or 24-bit recommended)

Macintosh

- MACINTOSH OS X 10.2.3, 10.3
- SAFARI 1.0 or higher
- 128 MB RAM
- 200 MB hard drive disk space available
- CD-ROM drive
- Available USB port
- Color monitor, 1024x768 pixels (thousands or millions of colors recommended)